Oil-Only Absorbency

Absorb oil- and petroleum-based fluids while repelling water

Oil-only absorbents are specially designed to clean-up oils and petroleum-based liquids while also repelling water and floating indefinitely.

Unaffected by temperature and impervious to rot and mildew, oil-only absorbents are an ideal choice for outdoor use, in bodies of water or anywhere that water may be inadvertently absorbed.

Oil-only absorbent family

All oil-only pads and rolls start with a highly absorbent polypropylene core. From there, it's all about the application. Product families feature different weights, coverstocks and finishing to provide the right solution for your needs.



Liquids absorbed

- Drilling and cutting fluids
- Hydraulic and brake fluids
- Engine oils
- Transmission fluids
- Lubricants

- Gasoline, diesel and aircraft fuels
- · Cooking oils
- Oil-based paints and solvents
- Other oils and petroleum-based fluids

Popular applications

- Outdoors
- Around bodies of water
- Wiping tools
- Small spills
- Under leaky pipes
- Around machinery
- Outdoor storage containers
- Under dripping valves
- Other general purpose maintenance









Oil-Only Absorbency



Product summary

Absorbs: Oils, coolants,

solvents and oil-based fluids

Coverstock: Top and bottom

coverstock (3-ply)

Durability: \checkmark \checkmark

Linting: Medium linting

Absorbencies: Heavy and medium

weight

Cost: \$\$\$

Recommended for

- Anywhere there is a leak, drip or spill
- Fuel stations and automotive industries
- Precision engineering
- Printing industries

Oil Plus Absorbents

Perfect for general everyday use and emergency spill clean-up.

- Oil-only absorbency for petroleum-based oils, solvents and other non-water soluble liquids
- Floats indefinitely even when saturated with oil
- 3-ply meltblown polypropylene construction increases durability and reduces lint

Additional features

- Perforated: Select exactly the size you need
- Dimpled: Adds durability and reduces linting







Oil Plus Pads

Pre-cut pads are ideal for wiping or catching drips.

Catalog #	Туре	Size	Perforated	Absorbency Factor (gl/gs)	Absorbency Capacity (gal)	Shipping Wt. (lbs)	Pallet Qty.	Quantity
OP50	Heavy-weight pad	30 in. x 30 in.	Yes, 15 in.	12.5	41	24	11	50/case
OP150DND	Heavy-weight pad*	15 in. x 19 in.	Yes, 7.5 in.	12.5	39	27	18	150/case
OP100	Heavy-weight pad	15 in. x 19 in.	Yes, 7.5 in.	12.5	26	17.5	30	100/case
OP300	Medium-weight pad	15 in. x 19 in.	Yes, 7.5 in.	12.5	20.5	14	30	100/case

^{*}Features Dispense-N-Dispose® System





Oil Plus Rolls

Continuous rolls are ideal for covering larger areas.

Perforations make it easy to select smaller sizes when needed.

Catalog #	Туре	Size	Perforated	Absorbency Factor (gl/gs)	Absorbency Capacity (gal)	Shipping Wt. (lbs)	Pallet Qty.	Quantity
OP30-DP	Heavy-weight roll	30 in. x 150 ft.	Yes, 15 in. and every 15 in.	12.5	49	33	12	1/case
OP30P	Heavy-weight roll	30 in. x 150 ft.	Yes, every 30 in.	12.5	49	33	12	1/case
OP30	Heavy-weight roll	30 in. x 150 ft.	No	12.5	49	33	12	1/case
OP15-DP	Heavy-weight roll	15 in. x 150 ft.	Yes, 7.5 in. and 12 in. across	12.5	24	17.5	24	1/case
OP15P	Heavy-weight roll	15 in. x 150 ft.	Yes, every 18 in.	12.5	24	17.5	24	1/case
OP15	Heavy-weight roll	15 in. x 150 ft.	No	12.5	24	17.5	24	1/case
OP350-DP	Medium-weight roll	30 in. x 150 ft.	Yes, 15 in. and every 15 in.	12.5	38	26.5	12	1/case
OP315P	Medium-weight roll	15 in. x 150 ft.	Yes, every 18 in.	12.5	19	14	24	1/case

Dispense-N-Dispose® System:

OP150DND features 150 heavy weight pads in a unique Dispense-N-Dispose® system — packaging doubles as a dispenser and a disposal bin all at once.



Chemical Application Guide

Polypropylene Products:

- Battlemat® Absorbents
- UXT Absorbents
- HT Absorbents
- MRO Plus® Absorbents
- GP Absorbents
- Basic Universal Absorbents
- SIR and BSM Mats
- AllWIK® SOCs and Pillows
- Cobra Coil® SOCs

Polypropylene Products:

- Oil-only SOCs and Pillows
- Trackmat Absorbents
- SXT® Oil Absorbents
- Oil Plus Absorbents
- SPC® Oil Absorbents • ENV® Oil Absorbents
- Basic Oil-only Absorbents
- Static Resistant Absorbents

- BRIGHTSORB™ High Visibility Absorbents
- Chemical Absorbents
- Universal Plus Absorbents
- HAZWIK SOCs and Pillows

Organic Eco-Friendly Products:

- Re-Form[™] Absorbents
- Re-Form Plus Absorbents
- Re-Form XPlus Absorbents
- Re-Form Oil-only Absorbents MULTIWIK® and SLIKWIK® SOCs
- SPC Granular
- · Re-Form Granular
- Rag Rug Absorbents

Chemical	Universal	Oil only	Chemical	Organic
Acetaldehyde	Χ		Χ	Χ
Acetic Acid	X		X	
Acetic Anhydride	X		X	
Acetone	X	Х	X	Χ
Acetyl Chloride	Χ		Χ	
Acrolein	X	Χ	X	
Acrylonitrile	X	/\	X	X
Allyl Alcohol	X		X	X
Aminobenzoic Acid	X		X	
Ammonia (Anhydrous)	X	Χ	X	X
Ammonium Hydroxide	X	X	X	X
Amyl Acetate	X	X	X	
Amyl Alcohol	X	/	X	X
Aniline	X		X	X
Antifreeze	X		X	X
Aqua Regia	X		X	
Aqueous Ammonia	X		X	
Aviation Fuel	X	Х	X	Χ
Benzene	X	X	X	X
Benzoic Acid	X	^	X	
Benzonitrile	X		X	
Benzoyl Chloride	X		X	
Benzyl Alcohol	X		X	X
Boric Acid	X		X	
Brake Fluid	X	Χ	X	Χ
Bromine	X	^	X	
Butyl Acetate	X	Х	X	
Butyl Alcohol	X	X	X	X
Butylamine	X	^	X	X
Butyric Acid	X	X	X	^
	X	^	X	
Carbolia Apid	X		X	
Carbolic Acid	X		X	
Carbon Disulfide		V		X
Carbon Tetrachloride	X	X	X	X
Castor Oil		^		٨
Chlorine Water	X		X	
Chloroacetic Acid			X	
Chlorobenzene	X	\ <u></u>		V
Chloroform	X	Χ	X	X
Chromic Acid (50%)	X		X	
Chlorosulfonic Acid	X		X	
Citric Acid	X		X	· ·
Clorox (Full Strength)	X	\ <u> </u>	X	X
Corn Oil	X	X	X	X
Cottonseed Oil	X	X	X	X
Cresol	X	X	X	X
Cyclohexane	X	Χ	X	X
Detergents	Χ		Χ	X

Chemical	Universa	Oil only	Chemica	Organic
Dichlorobenzene	Χ	Χ	Χ	
Diethylamine	Χ	Χ	Χ	
Diethyl Ether	Χ	Χ	Χ	Χ
Disooctyl Phthalate	Χ	Χ	Χ	Χ
Dinitrobenezene	Χ	Χ	Χ	
Dioxan	Χ		Χ	Χ
Electrolyte Fluid	Χ		Χ	
Ether	Χ	Χ	Χ	Χ
Ethyl Acetate	Χ	Χ	Χ	Χ
Ethyl Alcohol	Χ	Χ	Χ	Χ
Ethyl Benzene	Χ	Χ	Χ	
Ethyl Chloride	Χ	Χ	Χ	
Ethyl Ether	Χ	Χ	Χ	X
Ethyl Propionate	Χ	Χ	Χ	Χ
Ethylene Glycol	Χ		Χ	Χ
Flouorosilicic Acid	X		X	
Formaldehyde	Χ		Χ	Χ
Formic Acid	X		Χ	
Fuel Oil	X	Х	Χ	Χ
Gasoline	X	X	X	X
Gearbox Oil	X	Χ	X	Χ
Glacial Acetic Acid	X		X	
Glycerol	X	\ <u></u>	X	X
Heptane	X	X	X	X
Hexane	X	Χ	X	X
Hydrazine	X		X	
Hydrochloric Acid	X		Х	
Hydrogen Cyenide	X	X	X	
Hydrogen Cyanide Hydrogen Peroxide	X	^	X	X
Isobutyl Alcohol	X	X	X	X
Isobutyric Acid	X	X	X	^
Isopropyl Acetate	X	X	X	X
Isopropyl Alcohol	X	X	X	X
Kerosene	X	X	X	X
Keytones	X	X	X	X
Linseed Oil	X	X	X	X
Lubricating Oil	X	X	X	X
Magnesium Hydroxide	X		X	,,
Methyl Alcohol	X	Χ	X	Χ
Methyl Chloride	X	X	Χ	
Methyl Ether	X	X	X	Χ
Methyl Ethyl Ketone	X	X	X	X
Methyl Propionate	X	X	X	X
Mineral Oil	X	X	Χ	X
Motor Oil	X	X	X	X
Naphthalene	X	X	X	X
Nitrio Acid	V		V	

	niversal	il only		rganic
Chemical		0	0	0
Nitrobenzene	X		X	
Nitrobenzoic Acid	X		X	
Nitrotoluene	Χ	Χ	Χ	Χ
Octane	Χ	Χ	Χ	Χ
Oleic Acid	Χ	Χ	Χ	
Olive Oil	Χ	Χ	Χ	Χ
Paraffin	Χ	Χ	Χ	Χ
Perchloroethylene	Χ	Χ	Χ	Χ
Petroleum Ether	Χ	Χ	Χ	Χ
Phenol	Χ		Χ	Χ
Phosphoric Acid	Χ		Χ	
Plating Solutions	Χ		Χ	
Potassium Hydroxide	Χ		Χ	
Propanol	Χ		Χ	Χ
Propionic Acid	Χ	Χ	Χ	
Propyl Alcohol	Χ	Χ	Χ	Χ
Propylene Glycol	Χ	Χ	Χ	Χ
Quinoline	Χ		Χ	
Resorcinol	Χ		Χ	
Salt Solutions (metallic)	Χ		Χ	Χ
Silicone Oil	Χ	Χ	Χ	Χ
Silver Nitrate	Χ		Χ	Χ
Soap Solution (concentrated)	Χ	Χ	Χ	Χ
Sodium Bicarbonate	Χ		Χ	Χ
Sodium Bisulfite	X		X	,,
Sodium Chloride	X		X	Χ
Sodium Hydroxide	X		X	,,
Sodium Hypochlorite	X		X	Χ
Sodium Nitrate	X		X	X
Stannic Chloride	X		X	//
Starch	X		X	Χ
Styrene	X	Χ	X	X
Sucrose	X	/\	X	X
Sulfuric Acid	X		X	//
Synthetic Motor Oil	X	Χ	X	Χ
Tannic Acid	X	^	X	//
Toluene	X	Χ	X	Χ
Transformer Oil	X	X	X	X
Trichloroethylene	X	X	X	X
Triethylene Glycol	X	X	X	X
Turpentine	X	X	X	X
Urine	X	Λ	X	X
	X	X	X	X
Vinyl Acetate	X	^	X	X
Vinegar Xylene	X	Χ	X	X
Лунене	^	^	٨	^

Disclaimer: The above information is provided as a guide only. No claims or warranties are expressed or implied as to the absolute accuracy of the data supplied. In all cases it is assumed chemicals in question are at ambient temperatures and pressure and are used in basic state, not in combination or mixtures. Small test samplings by user is always recommended to ensure safe application.

Nitric Acid